

ST9721-U4

SEALED AUTOMOTIVE RELAY SOCKET FOR USE WITH AZ973 SHROUDED RELAY



FEATURES

- 5 - Way connector easily converts to 4-way
- Components are made from U.L. recognized materials
- Excellent chemical resistance
- V2 or better flammability rating
- Push to seat & seal terminals
- Universal fit for most sealed ISO relays
- Individual wires seals, 3 sizes fit all wire ranges
- Low cost

<i>TERMINAL CHART</i>		<i>WIRE Ga.</i>
<i>FCI AUTO.</i>	<i>AMP</i>	
JW-1230-2		12-14
JW-1630-2		16-18
	42100-	14-18
	42281-	14-18
	42904-	12-16
	60249-	12-16

<i>WIRE Ga.</i>	<i>SEAL CHART</i>	
	<i>Part #</i>	<i>Insulation O.D.</i>
	312xP	PLUG
		.in (mm) - .in (mm)
12-14	312x13	.134 (3.4) - .154 (3.9)
12-16	312x09	.102 (2.6) - .134 (3.4)
16-20	312x06	.063 (1.6) - .094 (2.4)

Notes

Size: 35, 6 Lx 30 Hx 35,6W

Color: Black

Material: Zytel 103 (socket) Nitrile (gasket) Santoprene 151 (seals)

AMERICAN ZETTLER, INC.

12/6/05W

PHONE: (949) 831-5000

www.azettler.com

E-MAIL: SALES@AZETTLER.COM

This specification provides an overview of the most significant part features. Any individual applications and operating conditions are not taken into consideration. It is recommended to test the product under application conditions. Responsibility for the application remains with the customer. Proper operation and service life cannot be guaranteed if the part is operated outside the specified limits.