

# AZ673

## MINIATURE POWER RELAY

### FEATURES

- Compact size for dense PCB layouts
- High power contacts (10A) for use in consumer appliances, HVAC, TV
- Withstands surges of up to 10,000 volts
- Epoxy sealed version available
- Insulation Class B standard
- UL/CUR file E44211
- TÜV file R50155379



### CONTACTS

<b>Arrangement</b>	1 Form A (SPST), 1 Form C (SPDT)
<b>Ratings</b>	Max. switched power: 300W or 2500VA Max. switched current: 10A Max. switched voltage: 150VDC* or 250 VAC <small>*Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.</small>
<b>Rated Load UL, CUR,</b>	10A at 250VAC, general use, 100k 10A at 30VDC resistive, 100K 1/8HP at 125VAC (1 Form C only) 1/4HP at 250VAC (1 Form C only) TV-5 at 125VAC (1 Form A only)
<b>TÜV</b>	10A at 250VAC resistive, 100k 10A at 30VDC resistive, 100k
<b>Material</b>	Silver cadmium oxide or silver tin oxide
<b>Resistance</b>	< 100 milliohms initially (6V, 1A voltage drop method)

### COIL

<b>Power At Pickup Voltage (typical)</b>	300mW standard coil 140mW sensitive coil
<b>Max. Continuous Dissipation</b>	1.2W at 20°C (68°F) ambient
<b>Temperature Rise</b>	48°C (86°F) at nominal coil voltage, std. coil 22°C (40°F) at nominal coil voltage, sens. coil
<b>Temperature</b>	Max. 130°C (266°F)

### NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.
4. Specifications subject to change without notice.

### GENERAL DATA

<b>Life Expectancy Mechanical Electrical</b>	1 x 10 <sup>7</sup> 1 x 10 <sup>5</sup> at 10A 240VAC Res.
<b>Operate Time (typical)</b>	15ms at nominal coil voltage
<b>Release Time (typical)</b>	5ms at nominal coil voltage (with no coil suppression)
<b>Dielectric Strength (at sea level for 1 min.)</b>	1000Vrms contact to contact 4000Vrms N.O. contact to coil 3000Vrms N.C. contact to coil 10,000V surge contact to coil
<b>Insulation Resistance</b>	1000 megohms min. at 20°C, 500VDC, 50% RH
<b>Dropout</b>	5% of nominal coil voltage
<b>Ambient Temperature Operating</b>	-40°C (-40°F) to 70°C (158°F)
<b>Storage</b>	-40°C (-40°F) to 105°C (221°F) sensitive coil -40°C (-40°F) to 130°C (266°F)
<b>Vibration</b>	1.5mm DA at 10–55 Hz
<b>Shock</b>	10 g
<b>Enclosure</b>	Plastic
<b>Terminals</b>	PC, tinned
<b>Max. Solder Temp.</b>	250°C (482°F)
<b>Max. Solder Time</b>	5 seconds
<b>Max. Solvent Temp.</b>	80°C
<b>Max. Immersion Time</b>	30 seconds
<b>Weight</b>	Approx. 12 grams

**AMERICAN ZETTLER, INC.**

[www.azettler.com](http://www.azettler.com)

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

# AZ673

## RELAY ORDERING DATA

COIL SPECIFICATIONS — STANDARD COIL				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	1 Form A	1 Form C
5	3.75	6.5	47	AZ673-1A-5D	AZ673-1C-5D
6	4.50	7.8	68	AZ673-1A-6D	AZ673-1C-6D
9	6.75	11.7	155	AZ673-1A-9D	AZ673-1C-9D
12	9.00	15.6	270	AZ673-1A-12D	AZ673-1C-12D
18	13.5	23.4	620	AZ673-1A-18D	AZ673-1C-18D
24	18.0	31.2	1080	AZ673-1A-24D	AZ673-1C-24D
48	36.0	62.4	4400	AZ673-1A-48D	AZ673-1C-48D

COIL SPECIFICATIONS — SENSITIVE COIL				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	1 Form A	
5	3.75	6.5	100	AZ673-1A-5DS	
6	4.50	7.8	145	AZ673-1A-6DS	
9	6.75	11.7	325	AZ673-1A-9DS	
12	9.00	15.6	575	AZ673-1A-12DS	
18	13.5	23.4	1300	AZ673-1A-18DS	
24	18.0	31.2	2310	AZ673-1A-24DS	

\*For epoxy sealed version add suffix "E". For silver tin oxide contacts add suffix "A". When suffix "E" is specified for Epoxy Seal, refer to AZ "Relay Technical Notes" on AZ website - Product Resources. Consult factory for other PCB process conditions that may apply.

## MECHANICAL DATA

FORM C VERSION SHOWN

DIM. LETTER	DIM. SEALED		DIM. UNSEALED	
	INCHES	MM	INCHES	MM
A	.965	24.5	.937	23.8
B	.413	10.5	.374	9.5
C	.093	2.4	.079	2.0
D	.059	1.5	.039	1.0

### PC BOARD LAYOUT

VIEWED TOWARD TERMINALS

### CIRCUIT DIAGRAM

VIEWED TOWARD TERMINALS

Dimensions in inches with metric equivalents in parentheses. Tolerance:  $\pm .010$ "