


AZ942A

20 AMP MINIATURE AUTOMOTIVE RELAY

FEATURES

- High switching capacity — 20 Amps
- DC coils to 24 VDC
- Epoxy sealed versions available
- Class F insulation for high temperature operation
- QS9000, ISO9001, ISO14001
- Extremely cost effective



CONTACTS

Arrangement	SPST (1 Form A) SPDT (1 Form C)
Ratings Medium Duty	Resistive load Max. switched power: 280 W or 5000 VA Max. switched current: 20 A Max. switched voltage: 30 VDC or 250 VAC
Material	Silver nickel
Resistance	<100 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power At Pickup Voltage (typical)	220 mW
Max Continuous Dissipation	2.2 W at 20°C (68°F) ambient
Temperature Rise	40°C (72°F) at nominal coil voltage
Temperature	Max. 155°C (311°F)

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Unsealed relays should not be dip cleaned.
4. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1x10 ⁷ 1 x 10 ⁵ at 20 A 14 VDC Res.
Operate Time (typical)	10 ms at nominal coil voltage
Release Time (typical)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	1500 Vrms contact to coil 1000 Vrms across contacts
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C(-40°F) to 105°C(221°F) -55°C(-67°F) to 155°C(311°F)
Vibration	0.062" DA at 10–55Hz
Shock	10 g operational, 100 g damage
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	12 g

AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

12/12/12


AZ942A

RELAY ORDERING DATA

STANDARD RELAYS				ORDER NUMBER*	
COIL SPECIFICATIONS				Unsealed	Sealed
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$		
6	3.2	9.9	45	AZ942A-1CT-6D	AZ942A-1CT-6DE
12	6.3	19.8	180	AZ942A-1CT-12D	AZ942A-1CT-12DE
24	12.6	39.8	720	AZ942A-1CT-24D	AZ942A-1CT-24DE

*Substitute "1AT" in place of "1CT" to indicate 1 Form A contact.

MECHANICAL DATA



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

12/12/12